

## Anziehmomente

<b>Nabe/Typ</b>	<b>Muttern</b>	<b>Anziehmoment Nm</b>		<b>Außendurchmesser der Mutter</b>
Technodrive	M16 X 2	70	Nm	32
PODZ 10	M10 X 1.5	25	Nm	32
	M27 X 2	400	Nm	40
10W	UNC 3/4"	70	Nm	40
ISO 20	M14 X 1.5	50	Nm	32
ISO 22	M16 X 1.5	70	Nm	32
ISO 25	M16 X 1.5	70	Nm	32
ISO 25-3	M16 X 1.5	70	Nm	32
ISO 30	M20 X1.5	135	Nm	32
ISO 30-3	M20 X 1.5	135	Nm	40
ISO 35-3	M24 X 2	250	Nm	40
ISO 35-4	M24 X 2	250	Nm	40
ISO 40-3	M24 X 2	250	Nm	40
ISO 40-4	M24 X 2	250	Nm	40
ISO 45 NAJAD	M33 X 2	300	Nm	44
ISO 45-3	M30 X 2	350	Nm	40
ISO 45-4	M30 X2	350	Nm	40
ISO 50	M36 X 3	300	Nm	44
SAE 1 3/4"-3	UNC 1¼"-7	430	Nm	40
SAE 1"	UNC 3/4"-10	125	Nm	32
SAE 1"-3	UNC 3/4"-10	125	Nm	40
SAE 1½"	UNC 3/4"-10	125	Nm	32
SAE 1½"-3	UNC 3/4"-10	125	Nm	40
SAE 1¼"	UNC 7/8"-9	160	Nm	32
SAE 1¼"-3	UNC 7/8"-9	160	Nm	40
SAE 1¾"-3	UNC 1"-8	250	Nm	40
SAE 1½"-3	UNC 1 ½"-7	200	Nm	40
SAE 2"-3	UNC 1½"-6	430	Nm	45
SAE 3/4"	UNC ½"-13	40	Nm	32
SAE 7/8"	UNC 5/8"-11	70	Nm	32
SD	M16 X 2	70	Nm	32
SD 40/50	M20 X 2	90	Nm	32
SD LOMB	M16 X 1.5 LOMB	60	Nm	32
SD Z25	M20 X 2	135	Nm	36
SD2C (M16)	M16 X 2	70	Nm	32
SD2C (M20)	M20 X 2	90	Nm	32
SD3	M16 X 2	70	Nm	32
SD33	M20 X 2	90	Nm	32
SD3C (M16)	M16 X 2	70	Nm	32
SD3C (M20)	M20 X 2	90	Nm	32
Swan	UNF 1"	250	Nm	40
Swan 10-38.1-3	M24 X 2	250	Nm	40
Swan 41 1¼"	UNC 3/4"-16	135	Nm	32
Yanmer 2BL & 3BL	UNC 5/8"-11	70	Nm	32
M8 Madenschraube	M8 X 10	10	Nm	8
M8 Keilbolzen	M8 X 25	12	Nm	8
M8 Sicherungsschraube	M8 X 20 (Sechskantmutter)	15	Nm	8
M8 Schraube für der Opferanode	M8 X 20	10	Nm	8
M6 Schraube für den Deckel	M6 X 16	5	Nm	6