

Torque settings for the shaft nut

Standard - Thread

M 14 x 2 UNC 1/2"-13	40 Nm / 30ft/lb
-------------------------	-----------------

M 16 x 2 BSW 5/8"-11 UNC 5/8"-11	60 Nm / 45ft/lb
--	-----------------

M 16 x 2 Yanmar Saildrive SD 20, 25 + SD31	60 Nm / 45ft/lb
--	-----------------

M 20 x 2,5 BSW 3/4"-10 UNC 3/4"-10	125 Nm / 95ft/lb
--	------------------

UNC 7/8"-9	160 Nm / 115ft/lb
------------	-------------------

M 22 x 1,5 M 24 x 3 BSW 1"-8 UNC 1"-8	210 Nm / 155ft/lb
--	-------------------

M 27 x 3	315 Nm / 230ft/lb
----------	-------------------

M 30 x 3,5 UNC 1 1/8"-7	350 Nm / 255ft/lb
----------------------------	-------------------

Torque settings for the shaft nut

Fine - Thread

M 14 x 1,5 BSF 1/2"-16	40 Nm / 30ft/lb
---------------------------	-----------------

M 14 x 1,5 BSW 5/8"-14 UNC 5/8"-18	70 Nm / 50ft/lb
--	-----------------

M 18 x 1,5 M 20 x 2 Yanmar Saildrive SD 40, 50 and 60	100 Nm / 75ft/lb
--	------------------

M 20 x 1,5 BSW 3/4"-12 UNC 3/4"-16	135 Nm / 100ft/lb
--	-------------------

M 24 x 2 BSF 1"-10 UNF 1"-12	225 Nm / 165ft/lb
------------------------------------	-------------------

M 30 x 2	430 Nm / 315ft/lb
----------	-------------------